

SHORT GALVANIZED COMPRESSION COUPLING

07-01038	3/8"
07-01050	1/2"
07-01075	3/4"
07-01100	1"
07-01125	1-1/4"
07-01150	1-1/2"
07-01200	2"
07-01250	2-1/2"
07-01300	3"



LONG GALVANIZED COMPRESSION COUPLING

07-02038	3/8"
07-02050	1/2"
07-02075	3/4"
07-02100	1"
07-02125	1-1/4"
07-02150	1-1/2"
07-02200	2"



LONG PVC COMPRESSION COUPLING

07-03038	3/8"
07-03050	1/2"
07-03075	3/4"
07-03100	1"
07-03125	1-1/4"
07-03150	1-1/2"
07-03200	2"
07-03250	2-1/2"
07-03300	3"
07-03400	4"



GALVANIZED COMPRESSION ELL

07-04038	3/8"
07-04050	1/2"
07-04075	3/4"
07-04100	1"
07-04125	1-1/4"
07-04150	1-1/2"
07-04200	2"



GALVANIZED COMPRESSION TEE

07-05038	3/8"
07-05050	1/2"
07-05075	3/4"
07-05100	1"
07-05125	1-1/4"
07-05150	1-1/2"
07-05200	2"



GALVANIZED COMPRESSION MALE ADAPTER

07-15038	3/8"
07-15050	1/2"
07-15075	3/4"
07-15100	1"
07-15125	1-1/4"
07-15150	1-1/2"
07-15200	2"



STYLE 38 DRESSER COUPLING

Red Shop Coat with Armored Gasket
Water, air most acids and alkaline.
Working pressure varies from 800 to 1500 P.S.I.
Working temperature 150°; 212° max

07-07050	1/2"	07-07250	2 1/2"
07-07075	3/4"	07-07300	3"
07-07100	1"	07-07400	4"
07-07125	1 1/4"	07-07500	5"
07-07150	1 1/2"	07-07600	6"
07-07200	2"	07-07800	8"



STYLE 39 INSULATED GAS DRESSER COUPLING

Red Shop Coat with Insulating Sleeve
Style 39 Dressers are the same as the Style 38 plus effective insulating properties. The insulating gasket has a skirt which extends under the follower ring to insulate it from the pipe. A "full boot" plastic tubular insulator inside the middle ring prevents contact of pipe-ends isolated from one another.

07-32200	2"
07-32250	2 1/2"
07-32300	3"
07-32400	4"
07-32500	5"
07-32600	6"
07-32800	8"



INSULATED DRESSER COMPRESSION COUPLING

Style 90 Insulating Coupling For Gas
Insulating sleeve and spacer made to conform to local codes.

07-09038	3/8"	07-09125	1 1/4"
07-09050	1/2"	07-09150	1 1/2"
07-09075	3/4"	07-09200	2"
07-09100	1"		



INSULATED DRESSER COMPRESSION COUPLING WITH 1/8" TAP AND PLUG

Style 90 Insulating Coupling For Gas
Insulating sleeve and spacer made to conform to local codes.
For Con Ed/Keyspan

07-22075	3/4" Ins. Dresser Coupling with 1/8" Tap and Plug
07-22100	1" Ins. Dresser Coupling with 1/8" Tap and Plug
07-22125	1 1/4" Ins. Dresser Coupling with 1/8" Tap and Plug
07-22150	1 1/2" Ins. Dresser Coupling with 1/8" Tap and Plug
07-22200	2" Ins. Dresser Coupling with 1/8" Tap and Plug



STYLE 90 DRESSER COUPLING WITH HIGH TEMPERATURE GASKETS

Cardboard Fiberglass Gaskets withstand temperatures up to 1200°. Good for commercial and industrial applications.

07-30050	1/2"
07-30075	3/4"
07-30100	1"
07-30125	1 1/4"
07-30150	1 1/2"
07-30200	2"



165 STEAM DRESSER COMPRESSION COUPLING

"Plus-Temp" High Temperature Compression Couplings
Rated to 350° at 150 PSI
Perfect for low-pressure steam repairs.
Grade 171 Butyl gaskets.

For oil and gas use grade 42 gaskets. Long Pattern

07-10038	3/8"	07-10125	1-1/4"
07-10050	1/2"	07-10150	1-1/2"
07-10075	3/4"	07-10200	2"
07-10100	1"		



STYLE 90 DRESSER COUPLING, ARMORED GASKET, E-COAT FINISH

07-14050	1/2" Style 90 Long Dresser Coupling
07-14075	3/4" Style 90 Long Dresser Coupling
07-14100	1" Style 90 Long Dresser Coupling
07-14125	1-1/4" Style 90 Long Dresser Coupling
07-14150	1-1/2" Style 90 Long Dresser Coupling
07-14200	2" Style 90 Long Dresser Coupling



STYLE 65 DRESSER COMPRESSION FITTINGS

FOR USE ON STEEL PIPES

Style 65 bodies are made of either steel or malleable iron; all coupling and fitting bodies conform to ANSI specifications for 150 psi rated fittings. The gasket retainer ring is made of steel.

Style 65 couplings should not be used for temperatures over 150°F

07-34050	1/2"
07-34075	3/4"
07-34100	1"
07-34125	1-1/4"
07-34150	1-1/2"
07-34200	2"



BRASS LEAD MAIN PACK JOINT COMPRESSION ADAPTER

07-11823	5/8 x 3/4 Lead Male Adapter
07-11833	3/4 x 3/4 Lead Male Adapter
07-11844	1 x 1 Lead Male Adapter
07-11855	1-1/4 x 1-1/4 Lead Male Adapter
07-11866	1-1/2 x 1-1/2 Lead Male Adapter
07-11877	2 x 2 Lead Male Adapter



BRASS PACK JOINT

COMPRESSION to MALE ADAPTERS

Compression seal with lock screw secures adapter to copper and converts to male thread.

07-248411	1/2" male x 1/2" copper
07-248431	3/4" male x 1/2" copper
07-248433	3/4" male x 3/4" copper
07-248443	1" male x 3/4" copper
07-248444	1" male x 1" copper
07-248455	1 1/4" male x 1 1/4" copper
07-248466	1 1/2" male x 1 1/2" copper
07-248455	2" male x 2" copper



BRASS PACK JOINT

COMPRESSION-to-COMPRESSION COUPLINGS

Compression seal with lock screw secures adapter to copper and make leak free connections.

07-264411	1/2" copper x 1/2" copper
07-264431	3/4" copper x 1/2" copper
07-264433	3/4" copper x 3/4" copper
07-264443	1" copper x 3/4" copper
07-264444	1" copper x 1" copper
07-264455	1 1/4" copper x 1 1/4" copper
07-264466	1 1/2" copper x 1 1/2" copper
07-264477	2" copper x 2" copper



07-288533	3/4" mips x 3/4" ips
07-288534	3/4" mips x 1" ips
07-288544	1" mips x 1" ips
07-288555	1 1/4" mips x 1 1/4" ips
07-288566	1 1/2" mips x 1 1/2" ips
07-288577	2" mips x 2" ips

BRASS PACK JOINT

COMPRESSION-to-COMPRESSION COUPLINGS

Compression seal with lock screw secures adapter to copper and make leak free connections.

07-295511	1/2" ips x 1/2" ips
07-295533	3/4" ips x 3/4" ips
07-295544	1" ips x 1" ips
07-295555	1 1/4" ips x 1 1/4" ips
07-295566	1 1/2" ips x 1 1/2" ips
07-295577	2" ips x 2" ips

