

GAS MAIN BURNER VALVE-TYPE A

AGA and CGA design certified for temperatures 32 to 125 deg F. Pilot tapped 1/8"fip for pilot cocks.

12-01150

12-01200

12-01250


| | not tappoa i/ |
|----------|---------------|
| 12-01050 | 1/2" |
| 12-01075 | 3/4" |
| 12-01100 | 1" |
| 12-01125 | 1¼" |
| | |

| 1 | pilot | COU |
|---|-------|-----|
| | | |
| | | |
| | | |
| | | |

1½" 2" 21⁄2 "







STOP AND WASTE CAP AND WASHER

12-03031 12-03038

12-02100

12-02200 12-02300

> 5/16" thread 3/8" thread

PILOT COCK-TYPE "B" AGA design certified and CGA listed.

Straight Right Angle

Left Angle

DRAIN KING

| | DRAIN KING |
|----------|--|
| | Unclogs drains as easily as turning on your faucet. |
| | Full line of reusable drain uncloggers * No harmful chemicals * |
| | Works where other methods won't * Safe, simple and easy to use * |
| | Environmentally safe |
| 12-05102 | 1" to 2" Drains * swimming pool lines * bathtubs and showers * |
| | bathroom sink * |
| 12-05203 | 2" to 3" Drains * kitchen sinks * showers * |
| | washing machine drains * bathtubs |
| 12-05304 | 3" to 4" Drains * main drains * outside deck drains * |
| | basement drains |
| 12-05306 | 3" to 6" Drains * main drains * outside sewer drains * |
| | basement drains |
| 12-05406 | 4" to 6" Drains * commercial drains * main sewer lines |
| | |
| 12-05608 | 6" to 8" Drains * commercial drains * main sewer lines |





SAFE-T-SEAL PLUGS

For pressure testing drain lines safe:pre-set pressure relief valve prevents over-inflation. air or water: can be used with either air or water. Versatile: most plugs fit more than one pipe size.

 12-08122
 1-1/4"-2" Safe-T-Seal Plug

 12-08300
 3" Safe-T-Seal Plug

 12-08101
 10"-12" Safe-T-Seal Plug

 12-08340
 3"-4" Safe-T-Seal Plug

 12-08460
 4"-6" Safe-T-Seal Plug

 12-08580
 5"-8" Safe-T-Seal Plug

 12-08142
 14"-24" Safe-T-Seal Plug

