

## HOSE BIBB VACUUM BREAKER

for all faucets where a portable hose could be attached.

13-04000	Hose Bibb Vac Breaker-Tripsco
13-04500	Hose Bibb Vac Breaker-Conbraco
13-04505	CP Hose Bibb Vac Breaker-Conbraco
13-04600	Frost Free Hose Bibb Vac Breaker-Conbraco



## HOT WATER HEATER DRAIN VALVES-BRASS

13-08150	Hot Water Heater Drain Valve 1-1/2" post
13-08300	Hot Water Heater Drain Valve 3" post



## ATMOSPHERIC TYPE VACUUM BREAKER

Application: Back-Siphonage \* Low Hazard Cross-Connections  
 Features: Corrosion resistant \* Rough brass or polished chrome finish  
 Suitable for hot or cold water service (up to 212 F at 125 PSI)  
 Compact and lightweight \* Durable \* Easy to maintain  
 Heat resistant silicone seat disc

13-02020	1/2" RB Vacuum Breaker	13-02021	1/2" CP Vacuum Breaker Conbraco
13-03025	1/4" RB Vac Breaker	13-03026	1/4" CP Vac Breaker
13-03038	3/8" RB Vac Breaker	13-03039	3/8" CP Vac Breaker
13-03050	1/2" RB Vac Breaker	13-03051	1/2" CP Vac Breaker
13-03075	3/4" RB Vac Breaker	13-03076	3/4" CP Vac Breaker
13-03100	1" RB Vac Breaker	13-03101	1" CP Vac Breaker
13-03125	1 1/4" RB Vac Breaker		
13-0315	1 1/2" RB Vac Breaker		
13-03200	2" RB Vac Breaker		



## APOLLO BALL VALVE

all bronze valve, Teflon seats and chrome plated ball, 600# WOG copper

	IPS
13-05038	1/4"
13-05050	3/8"
13-05075	1/2"
13-05100	3/4"
13-05125	1"
13-05150	1 1/4"
13-05200	1 1/2"
13-05250	2"
13-05300	2 1/2"
	3"



## APOLLO INTERNATIONAL

Apollo International is an economical forged brass full port ball valve that is UL listed and CSA approved.  
 Triple "S" stocks thread and sweat connection valves.  
 1/4" - 2" 600CWP, 2 1/2" - 4" 400CWP non-shock.

Copper	IPS
1/4"	13-15025
3/8"	13-15038
1/2"	13-15050
3/4"	13-15075
1"	13-15100
1-1/4"	13-15125
1-1/2"	13-15150
2"	13-15200
2-1/2"	13-15250
3"	13-15300
4"	13-15400



## TRIPSCO BALL VALVE

bronze ball valve, Teflon seats and chrome brass ball

Copper	IPS
1/4"	13-10025
3/8"	13-10038
1/2"	13-10050
3/4"	13-10075
1"	13-10100
1-1/4"	13-10125
1-1/2"	13-10150
2"	13-10200



## HOT WATER HEATER VACUUM RELIEF VALVE Conbraco

Automatically vents a system if a vacuum should occur. Prevents siphoning of the water from the system and collapse of a tank.

13-07050	1/2"
13-07075	3/4"



## ATMOSPHERIC BACKFLOW PREVENTER

13-20050	1/2"
----------	------



## FEED WATER PRESSURE REGULATOR/BACKFLOW ASSEMBLY Conbraco

13-22050  
 High capacity boiler feed valve features a corrosion-resistant, all-bronze body and spring cage and stainless steel integral strainer. The screw in bonnet eliminates the danger of corroding fasteners.  
 Completely corrosion resistant. Built in check prevents draw down when supply pressure falls.  
 Raise lever for fast fill boiler start up; return to normal position for normal fill.

- Adjusts from 10 to 25 psig
- Maximum temperature: 210°F
- Maximum Supply Pressure: 100 psig
- Standard setting: 15 psig
- NPT or union connections



## DUAL CHECK BACKFLOW PREVENTER

13-24050 1/2"  
 Dual check backflow preventers provide protection from cross-connections of non-potable water into safe drinking water systems by containment at the water meter. It operates in the horizontal or vertical position and under intermittent or continuous pressure. It is a compact and economical device that consists of two independently acting spring loaded check valves.



## BACKFLOW PREVENTER

13-12050	1/2"
----------	------

